

## Performance Specifications

DECCO Solenoid 60 Hz Force Characteristics (in Pounds)

MODELS	QUIET HOLDS	STROKE IN INCHES											APPROX SHIP WT.	PAGE	
		.13	.19	.25	.31	.38	.44	.50	.63	.75	.88	1.0			
01	4.75			2.20		1.85		1.75						.38	5
02	5.50			3.10		2.60		2.40						.44	5
15	8.00			5.25		4.60		4.50						1.00	6-7
16	12.00	4.10		6.75		6.50		6.40						1.13	6-7
17	16.00	5.00		9.00		8.10		8.00						1.25	6-7
18	18.50	7.00	2.75	11.40	1.95	10.50	1.75	10.25						1.63	6-7
20	25.00	8.50	3.90	13.50	2.80	12.50	2.50	12.50	12.50	12.25				3.50	8-9
21	35.00	11.00	5.80	16.00	4.75	15.00	4.50	15.00	15.00	15.00				3.63	8-9
51	40.00	14.50	7.15	23.00	6.60	21.00	6.50	20.00	20.00	20.00	20.00	20.00	20.00	4.63	8-9
52	45.00	18.00	9.90	28.00	8.50	25.00	8.00	25.00	25.00	25.00	25.00	25.00	25.00	5.13	8-9
53	50.00	20.00	12.25	37.00	11.00	32.00	10.25	30.00	30.00	30.00	30.00	30.00	30.00	5.63	8-9

